



SM (CABLES)

Low voltage wiring, flexible and special cables



STANDARDS

EN50525-2-11
EN60228
EN60227-3
EN50265-2-1
IEC60227-5
IEC60332-1-2



Light Duty Round Cable, H03VV-F

CONSTRUCTION (Cu/PVC/PVC)

- Conductor**
Flexible multi-stranded copper (Class 5)
- TI 2 PVC**
Insulation
Polyvinyl chloride Type: TI2
- TM 2 PVC**
Sheath
Polyvinyl chloride Type: TM2

SPECIFICATIONS

- 70°C** Maximum operating temperature
- 2KV** AC Test Voltage
- 160°C** Maximum short circuit temperature
- 6 X D** Minimum Bending Radius
- 300/300V** Rated voltage Uo/U
- Flame propagation test on single cable. Euroclass Eca.**

APPLICATIONS

Used in dry and humid areas under low to medium mechanical stress, generally used as a hookup cable for household appliances and electronic equipment.

MARKING

Printed with CIJ in Black or white indelible ink.

SM (CABLES) to BS EN 50525-2-11 03VV-F ###SQ MM 300/300V Eca CE

TECHNICAL DATA

Product Code	Nominal Cross Section mm ²	Overall Dimensions mm	Approximate Net Weight kg/km	Maximum Conductor Resistance Ω/km @ 20°C	Current Carrying Capacity in Air Amperes (A)
H03VV-F 300/300V					
SM03VVF2X0/50	2 x 0.5	4.6	36	39	3
SM03VVF2X0/75	2 x 0.75	4.9	46	26	6
SM03VVF3X0/50	3 x 0.5	4.9	43	39	3
SM03VVF3X0/75	3 x 0.75	5.2	54	26	6
SM03VVF4X0/50	4 x 0.5	5.4	53	39	3
SM03VVF4X0/75	4 x 0.75	5.7	68	26	6

FLEXIBLE SHEATHED CABLE

Specifications and technical data is provided in good faith and is believed to be correct at the time of publication. Actual products may differ in dimensions due to manufacturing tolerances. The information provided within this document is typical and is intended for guidance only. This specification and data is subject to changes without notice or liability.

T: +356 21 697 888

www.smcables.com
info@smcables.com